

RECEIVER

# R5 YOUR SECURE CONNECTION TO THE MACHINE



arcon

## R5

### EASY AND QUICK TO CONFIGURE

Most of ARCON's receivers are fitted with a programmable motherboard. This enables the ARCON Team to respond to customer requests as fast as possible and offers maximum flexibility.



The R5 is the universal housing of ARCON. This design has many digital standard receivers. With the R5 housing variant, analogue outputs can be conveniently implemented for control in loading cranes or special machines. One of our standard proportional receivers is ideal for this type of application.

<b>INTERFACES:</b>	STOP-output (up to cat. 3 Ple / SIL 3) RS 232/485, CANopen, DeviceNet, J1939, Profibus, Industrial Ethernet, relay outputs, transistor outputs voltage outputs, current outputs
<b>PROTECTION CLASS:</b>	IP 65
<b>TEMPERATURE RANGE:</b>	-20 up to +70° C
<b>WEIGHT:</b>	approx. 1800g
<b>DIMENSIONS:</b>	245 x 165 x 90 mm
<b>FREQUENCY RANGE:</b>	419/429/432-481/863-930MHz; 2.4GHz
<b>OPERATING VOLTAGE:</b>	8-30 VDC, 48/115/230VAC depending on equipment

