

T5

COMPACT ALL-ROUNDER

CERTIFIED THROUGH:

- EN ISO 13849
- EN 60204-32
- EN 62061
- EN 62745
- DNV



Thanks to its balanced size ratio, the T5 transmitter can be equipped with a variety of operating elements and information sources. The freely programmable GDC 3.5 colour graphic display can be easily integrated.

TECHNICAL DATA

PROTECTION CLASS	IP 65
TEMPERATURE RANGE	-20 to +60 °C
WEIGHT	approx. 1800 g
DIMENSIONS	290 x 180 x 155 mm (W/D/H)
FREQUENCY RANGE	432-481/863-930 MHz; 2.4 GHz
BATTERY TECHNOLOGY	Exchangeable battery, NiMH or Li-Ion
OPERATING TIME	up to 20 hours
OPERATING RANGE	> 100 m

OPTIONS

- STOP Cat. 3 PLe / SIL3
- Safe digital control functions up to Cat. 3 PLe / SIL3
- Safe analogue control functions up to Cat. 3 PLe / SIL3
- 3.5" colour graphic display freely programmable via QT
- Graphic display 2.1"
- Graphic display 2.8"
- LED feedback
- Video transmission from up to 4 cameras in real time
- Brightness sensor
- Tilt sensor
- Presence sensor
- Vibration alarm
- Control panel lighting
- Cable control with optional charging function
- CAN cable control
- Multi-operation
- User-defined switch-off time
- Customised labelling
- Bottom housing available in red, blue or grey
- Shoulder hook
- Shoulder cross belt
- Belly belt
- Neck belt

